

CHROME FLOWMETERS



The hospital standard in flowmeters

They're Durable...

The polycarbonate housings are extremely durable. They are impervious to chemical solutions normally used in a clinical setting preventing clouding and spidering. The polycarbonate flow tubes insure durability.

They're Accurate...

Our flowmeters use black glass flow indicator balls. Their exceptional sphericity and uniform weight contribute to a more accurate flowmeter than those using plastic floats.

They're Precise...

Highly accurate needle valves insure precise flow-settings the first time....every time.

They're Easy to Use...

The flow control knob is on the front of the flowmeter in clear sight of the operator unlike side mount knobs which are susceptible to damage during installation of additional equipment. Our black glass float makes the flow setting easy to read.

They're Dependable...

The housings and flow tubes carry a lifetime warranty and the needle valves carry a five (5) year warranty.



SPECIFICATIONS

| Model | Gas | Scale | Increments | Accuracy | |
|----------|--------|----------|---|--|--|
| 0-5 lpm | Oxygen | 0-5 lpm | .25 lpm (starts at .5 lpm) | ±.20 lpm | |
| 0-8 lpm | Oxygen | 0-8 lpm | .5 lpm (starts at .5 lpm) | ±.25 lpm | |
| 0-15 lpm | Oxygen | 0-15 lpm | .5 lpm from .5 to 5 lpm 1 lpm from 5 to 15 lpm | ±.25 lpm from .5 to 5 lpm ±.5 lpm above 6 to 15 lpm | |
| 0-15 lpm | Air | 0-15 lpm | .5 lpm from .5 to 5 lpm 1 lpm from 5 to 15 lpm | ±.25 lpm from .5 to 5 lpm ±.5 lpm above 6 to 15 lpm | |
| 0-70 lpm | Oxygen | 0-70 lpm | 5 lpm (starts at 10 lpm) | ±3 lpm with Flush | |
| 0-70 lpm | Air | 0-70 lpm | 5 lpm (starts at 10 lpm) | ±3 lpm with Flush | |

Flowmeters calibrated at 50 PSI, 70°F, standard atmospheric pressure. Specifications are subject to change without prior notice.

ORDERING INFORMATION

| | | O2 0-5 LPM | O2 0-8 LPM | O2 0-15 LPM | Air 0-15 LPM | O2 0-70 LPM | Air 0-70 LPM |
|--------------|---------------------------|---------------|---------------|----------------|-----------------|----------------|-----------------|
| | No Adaptor (1/8 NPTF) | 1MFA3501 | 1MFA4001 | 1MFA1001 | 1MFA2001 | 1MFA8001 | 1MFA9001 |
| | DISS Female Hex Nut | 1MFA3502 | 1MFA4002 | 1MFA1002 | 1MFA2002 | 1MFA8002 | 1MFA9001 |
| | DISS Female Hand Tight | 1MFA3503 | 1MFA4003 | 1MFA1003 | 1MFA2003 | 1MFA8003 | 1MFA9003 |
| C\$ = | DISS Male | 1MFA3504 | 1MFA4004 | 1MFA1004 | 1MFA2004 | 1MFA8004 | 1MFA9004 |
| | Ohmeda | 1MFA3505 | 1MFA4005 | 1MFA1005 | 1MFA2005 | 1MFA8005 | 1MFA9005 |
| 1 | Chemetron | 1MFA3506 | 1MFA4006 | 1MFA1006 | 1MFA2006 | 1MFA8006 | 1MFA9006 |
| | Oxequip | 1MFA3507 | 1MFA4007 | 1MFA1007 | 1MFA2007 | 1MFA8007 | 1MFA9007 |
| - | Puritan-Bennett | 1MFA3508 | 1MFA4008 | 1MFA1008 | 1MFA2008 | 1MFA8008 | 1MFA9008 |
| | Schrader | 1MFA3509 | 1MFA4009 | 1MFA1009 | 1MFA2009 | 1MFA8009 | 1MFA9009 |



ISO 9001 Certified Precision Medical, Inc. 300 Held Drive • Northampton, PA 18067 Phone: 610-262-6090 Toll-Free Phone: 1-800-272-7285 Fax: 610-262-6080 Toll-Free Fax: 1-800-352-1240 Visit us on the Web: www.precisionmedical.com 50338rev2 6/05 7.5M Printed in USA